

product guarantee¹




linear performance guarantee¹




ECO SMART LINE P60/260 - 280 W

Polycrystalline module family



Longlife tested



Power proofed



Safety provided



Selection of components



Cross-linking degree test



Performance surplus of 0 Wp to 6.49 Wp



Imp sorting



Special packing to avoid micro cracks in the cells



German warrantor

The 60-cell module Eco Smart Line like every Luxor solar module has high-quality solar cells with highest efficiency at the best possible low light behaviour to ensure the best energy output. Using intelligent electronics that is integrated into the junction box, the Eco Smart Line modules have a better overall system yield, provide greater flexibility in system design, more safety and better transparency in system monitoring.

Mismatch losses that occur due to different roof inclinations or partial shading can be avoided thanks to the Maximum Power Point Tracking (MPPT). The smart electronics in the junction box ensures that each module delivers its maximum performance. Since the PV system has lesser BOS components, thanks to Eco Smart Line, the installation is quicker, easier and cheaper.

ECO SMART LINE P60/260 - 280W



Polycrystalline module family

Module type LX - XXXP/156-60+ | XXX = Rated power Pmpp

Electrical data at STC

| | | | | | |
|------------------------------------|--------|--------|--------|--------|--------|
| Rated power Pmpp [Wp] | 260.00 | 265.00 | 270.00 | 275.00 | 280.00 |
| Pmpp range to | 266.49 | 271.49 | 276.49 | 281.49 | 286.49 |
| Rated current Impp [A] | 8.51 | 8.60 | 8.68 | 8.77 | 8.86 |
| Rated voltage Vmpp [V] | 30.65 | 30.90 | 31.16 | 31.42 | 31.68 |
| Short-circuit current Isc [A] | 9.01 | 9.09 | 9.18 | 9.27 | 9.35 |
| Open-circuit voltage Uoc [V] | 37.80 | 38.06 | 38.32 | 38.58 | 38.84 |
| Efficiency at STC | 16.03% | 16.33% | 16.63% | 16.94% | 17.25% |
| Efficiency at 200 W/m ² | 15.60% | 15.90% | 16.21% | 16.52% | 16.84% |

Electrical data at NOCT

| | | | | | |
|-------------------------------|--------|--------|--------|--------|--------|
| Pmpp [Wp] | 193.17 | 196.75 | 200.40 | 204.12 | 207.90 |
| Rated current Impp [A] | 6.81 | 6.88 | 6.95 | 7.02 | 7.09 |
| Rated voltage Vmpp [V] | 28.37 | 28.61 | 28.85 | 29.08 | 29.32 |
| Short-circuit current Isc [A] | 7.21 | 7.28 | 7.34 | 7.41 | 7.48 |
| Open-circuit voltage Uoc [V] | 34.99 | 35.23 | 35.47 | 35.71 | 35.96 |

Specification as per STC (Standard test conditions): irradiance 1000W/m² | module temperature 25°C | AM = 1,5

NOCT (nominal operating cell temperature): irradiance 800W/m² | wind speed 1m/sec | temperature 20°C | @45 +/- 2°C | AM = 1,5

Limiting values

| | |
|----------------------------------|--|
| Max. system voltage [V] | 1000 V |
| Max. return current [I] | 15 A |
| Operating Temperature | -40 to 85°C |
| Snow-load zone ² | approval up to SLZ 3 (according to DIN 1055) |
| Max. pressure load (static) [Pa] | 5400 |
| Max. dynamic load [Pa] | 2400 |

Temperature coefficient

| | |
|---|-------------------------------------|
| Temperature coefficient [V] [I] [P] | -0,30% /°C 0,05% /°C -0,41% /°C |
|---|-------------------------------------|

Specifications

| | |
|---|---|
| Number of cells (matrix) | 6 x 10, three strings in a row 156 mm x 156 mm |
| Module dimensions (L x W x H) ³ Weight | 1640 mm x 992 mm x 35 mm 20 kg |
| Front-side glass | 3.2 mm hardened solar glass with low iron content |
| Frame | stable, anodised aluminium frame in a hollow-section design |
| Junction Box | Tigo |
| Cable | 4 mm ² solar cable, cable length 1.0 m |
| Diodes | 3 Schottky Diodes 15A/45V |
| Connectors | MC4 or equivalent (IP67) |
| Hail test (max. hailstorm) | ∅ 45 mm impact velocity 23 m/s ± 83 km/h |

The specifications and average values can vary slightly. What is important is the corresponding data of the individual measurement. Specifications are subject to change without notice. Measurement tolerance: rated power +/- 3%, other values +/- 10%, all information in this data sheet corresponds to DIN 50380. A potential light-induced degradation of the power after commissioning is not considered here, other information can be found in the installation guidelines.


1 The specific warranty conditions are given under www.luxor-solar.com/download.htm

2 For standing installation

3 Tolerance L/W = +/- 3 mm, H = the dimensions given in the order confirmation will be decisive

4 Location on request


Back - / Front - / Side view³




- A: 4 x drainage 10*10 mm
- B: 8 x ventilation aperture 3*7 mm
- C: 8 x mounting hole⁴ d = 7 mm
- D: 2 x earthing d = 2 mm

Electrical characteristics

UI-diagram e.g. LX-270P/156-60+



UP-diagram e.g. LX-270P/156-60+



Luxor, your specialised company

Guidelines: 2006/95/EG-2006/95/EC,89/336/EWG-89/336/EEC,93/68/EWG-93/68/EEC



The validity of the certificates/listings for a specific country has to be examined under:
www.luxor-solar.com/download.htm